

1. Unique identification code of the product-type:

guttabeta® Star 400

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Flexible sheets for waterproofing - Plastic and rubber damp proof sheets including plastic and rubber basement tanking sheet

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Gutta Werke GmbH, Bahnhofstrasse 51-57, D-77746 Schutterwald www.gutta.com

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 2+

5. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

SKZ – Testing GmbH, 97076 Würzburg (Nr. 1213) performed the initial inspection and material testing under system 2+ and issued certificate of constancy of performance, certificate of conformity of the factory production control, test/calculation

6. Declared performance:

Essential characteristics	Performance	Test standard	Harmonised technical specification
Reaction to fire	F	EN 13501-1	DIN EN 13967:2012
Resistance to water penetration	passed	EN 1928	
Tear resistance	NPD	EN 12310-1	
Shear resistance of joints	NPD	EN 12317-2	
Resistance to impact	NPD	EN 12691	
Tensile strength	length > 210 N/50 mm cross > 170 N/50 mm	EN 12311-2	
Resistance against Static load	NPD	EN 12730	
Durability - of Water tightness against ageing - of Water tightness against alkali	NPD	EN 1928	
Dangerous substances	NPD		

NPD = No Performance Determined

7. The performance of the above product corresponds to the declared performance. The manufacturer is responsible for the production of this service declaration in accordance with the provisions of Regulation (EU) No. 305/2011. Signed for the manufacturer and on behalf of the manufacturer:



Schutterwald, dated 01.04.2017
(Place and Date)

Detlef Witte – Managing Director
(Name and Position)